

View Online at <https://aerobasegroup.com/nsn/5306-01-588-5415>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.413 inches and 0.463 inches

Fastener Length:

Between 2.548 inches and 2.578 inches

Head Style:

Dished hexagon

Head Height:

Between 0.156 inches and 0.171 inches

Width Between Flats:

Between 0.492 inches and 0.502 inches

Grip Diameter:

Between 0.311 inches and 0.312 inches

Thread Diameter:

0.312 inches

Grip Length:

Between 2.115 inches and 2.135 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Product Name:

Bolt, tension, hex head, close tolerance, a286 cres, short thread, reduced major thread diam., nonlocking, 160 ksi ftu

Special Features:

Drilled shank, drilled head

Material:

Stainless steel

Material Specification:

Ams5731 assn standard single material response or ams5732 assn standard single material response or ams5737 assn standard single material response or ams5853 assn standard single material response

Thread Series Designator:

Unjf

Specification Data:

80205-nas6305 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0