## NSN 5306-01-588-5427

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-588-5427 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.365 inches and 0.375 inches **Fastener Length:** Between 1.730 inches and 1.760 inches **Head Style:** Hexagon **Head Height:** Between 0.125 inches and 0.140 inches Width Between Flats: Between 0.429 inches and 0.439 inches **Grip Diameter:** Between 0.2490 inches and 0.2495 inches **Thread Diameter:** 0.250 inches **Grip Length:** Between 1.365 inches and 1.385 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Product Name:** Bolt, tension, hex head, close tolerance, 6al-4v titanium alloy, short thread, reduced major thread diameter, nonlocking, 160 ksi ftu **Special Features:** Unplated having drilled head Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas6404 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

## NSN 5306-01-588-5427

Shear Bolt - Page 2 of 2



Fiig:

A003b0