

View Online at <https://aerobasegroup.com/nsn/5306-01-589-6797>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.323 inches

**Fastener Length:**

4.698 inches

**Head Style:**

Hexagon

**Head Height:**

0.335 inches

**Width Between Flats:**

Between 0.367 inches and 0.376 inches

**Grip Diameter:**

Between 0.1890 inches and 0.1895 inches

**Point Diameter:**

Between 0.1810 inches and 0.1840 inches

**Shank Unthreaded Hole Diameter:**

0.075 inches

**Point Style:**

Flat

**Thread Diameter:**

0.190 inches

**Grip Length:**

4.375 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

4.534 inches

**Material:**

Iron alloy 660

**Material Specification:**

Ams 5732 assn standard single material response or ams 5731 assn standard single material response or ams 5737 assn standard single material response or ams 5853 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Ams 2700, method 1, type 2 or 8, class 1 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0