

View Online at <https://aerobasegroup.com/nsn/5306-01-590-3999>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.619 inches

**Fastener Length:**

0.619 inches

**Head Style:**

Double hexagon extended washer

**Head Height:**

0.388 inches

**Width Between Flats:**

Between 0.430 inches and 0.439 inches

**Extended Washer Diameter:**

0.644 inches

**Extended Washer Thickness:**

0.091 inches

**Hole Diameter:**

0.055 inches

**Grip Diameter:**

Between 0.3735 inches and 0.3745 inches

**Thread Diameter:**

0.375 inches

**Grip Length:**

2.000 inches

**Hole Quantity:**

4

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

17100 pounds per square inch

**Hardness Rating:**

390.0 rockwell c and 43.0 rockwell c

**Hole Configuration Style:**

Double hexagon longitudinal hole

**Material:**

Steel comp 4140 or steel comp 4340 or steel comp 8740

**Material Specification:**

Ams 6382 assn standard single material response or ams 6415 assn standard single material response or ams 6322 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Nas 672 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0