## NSN 5306-01-591-8806

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-591-8806

| Thread Class:   |
|---|
| 3a  |
| Thread Direction:   |
| Right-hand  |
| •   |
| Thread Length:  |
| 1.005 inches  |
| Fastener Length:  |
| 3.770 inches  |
| Head Style:   |
| Double hexagon extended washer  |
| Head Height:  |
| 0.472 inches  |
| Extended Washer Thickness:  |
| 0.090 inches  |
| Grip Diameter:  |
| 0.687 centimeters   |
| End Application:  |
| F-16 aircraft   |
| Thread Diameter:  |
| 0.625 inches  |
| Grip Length:  |
| 2.750 inches  |
| Thready Qty Per Inch (tpi):   |
| 18  |
| Min. Tensile Strength (psi):  |
| 59900 pounds per square inch  |
| Hardness Rating:  |
| 46.0 rockwell c and 50.0 rockwell c   |
| Material:   |
| Steel comp h11  |
| Material Specification:   |
| Ams6487 assn standard single material response                              |
| Surface Treatment:  |
| Cadmium   |
| Surface Treatment Specification:  |
| Mil-c-8837 type ii class 2 military specification single treatment response |
| Thread Series Designator:   |
| Unjf  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| Unit Ut Measure.  |
|   |

## NSN 5306-01-591-8806

Close Tolerance Bolt - Page 2 of 2



## Demilitarization:

Yes - demil/mli

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.