NSN 5306-01-592-3240

Shear Bolt - Page 1 of 2

Thread Class:

Right-hand

Thread Direction:

material response

За



View Online at https://aerobasegroup.com/nsn/5306-01-592-3240

| Inread Length: |
|---|
| 0.619 inches |
| Fastener Length: |
| 2.417 inches |
| Head Style: |
| Spline extended washer |
| Head Height: |
| 0.388 inches |
| Extended Washer Diameter: |
| 0.644 inches |
| Extended Washer Thickness: |
| 0.091 inches |
| Hole Diameter: |
| 0.055 inches |
| Grip Diameter: |
| 0.3735 mils and 0.3745 centimeters |
| Head Minor Diameter: |
| 0.438 inches |
| Thread Diameter: |
| 0.375 inches |
| Grip Length: |
| 1.798 inches |
| Hole Quantity: |
| 4 |
| Hole Type: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 24 |
| Min. Tensile Strength (psi): |
| 180000 pounds per square inch |
| Hardness Rating: |
| 39.0 rockwell c and 43.0 rockwell c |
| Hole Configuration Style: |
| Double hexagon longitudinal hole |
| Material: |
| Steel comp 4140 or steel comp 4340 or steel comp 8740 |
| Material Specification |

Ams6382 assn standard single material response or ams6415 assn standard single material response or ams6322 assn standard single

NSN 5306-01-592-3240

Shear Bolt - Page 2 of 2

Fiig: A003b0



| Surface Treatment: |
|--|
| Cadmium |
| Surface Treatment Specification: |
| Nas672 assn standard single treatment response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |