

View Online at <https://aerobasegroup.com/nsn/5306-01-592-5604>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.425 inches

**Fastener Length:**

1.800 inches

**Head Style:**

Hexagon

**Head Height:**

0.125 inches

**Width Between Flats:**

0.429 mils and 0.439 centimeters

**Hole Diameter:**

0.046 inches

**Grip Diameter:**

0.2485 mils and 0.2495 centimeters

**Point Diameter:**

Between 0.241 inches and 0.244 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches first hole

**Point Style:**

Flat

**Thread Diameter:**

0.250 inches

**Grip Length:**

1.375 inches

**Hole Quantity:**

3

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hole Configuration Style:**

Hexagon corners

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.122 inches first hole

**Material:**

Iron alloy 660

**Material Specification:**

Ams5731 assn standard single material response or ams5732 assn standard single material response or ams5737 assn standard single material response or ams5853 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type ii, class 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0