## NSN 5306-01-593-0967

Shear Bolt - Page 1 of 2





## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

Between 0.365 inches and 0.375 inches

#### Fastener Length:

Between 0.980 inches and 1.010 inches

#### **Head Style:**

Dished hexagon

#### **Head Height:**

Between 0.125 inches and 0.140 inches

#### Width Between Flats:

Between 0.429 inches and 0.439 inches

#### Grip Diameter:

Between 0.2641 inches and 0.2651 inches

#### **Thread Diameter:**

0.250 inches

## Grip Length:

Between 0.615 inches and 0.635 inches

## Thready Qty Per Inch (tpi):

28

## Min. Tensile Strength (psi):

160000 pounds per square inch

#### Surface Finish:

32.0 microinches threads

## Material:

Titanium alloy uns r56400

## **Material Specification:**

Ams4928 assn standard single material response or ams4967 assn standard single material response

#### Surface Treatment:

Aluminum

## Surface Treatment Specification:

Nas4006 assn standard single treatment response

## **Thread Series Designator:**

Unjf

Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

# NSN 5306-01-593-0967

Shear Bolt - Page 2 of 2

Fiig: A003b0

