## NSN 5306-01-593-3019

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-593-3019 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.523 inches and 0.533 inches **Fastener Length:** Between 3.138 inches and 3.183 inches **Head Style:** Dished hexagon **Head Height:** Between 0.250 inches and 0.265 inches Width Between Flats: Between 0.741 inches and 0.752 inches **Grip Diameter:** Between 0.5141 inches and 0.5151 inches **Thread Diameter:** 0.500 inches **Grip Length:** Between 2.365 inches and 2.385 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch **Surface Finish:** 32.0 microinches threads Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Nas4006 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5306-01-593-3019

Shear Bolt - Page 2 of 2



Fiig:

A003b0