

View Online at <https://aerobasegroup.com/nsn/5306-01-594-9262>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.840 inches

Fastener Length:

Between 3.353 inches and 3.383 inches

Head Style:

Hexagon

Head Height:

Between 0.281 inches and 0.296 inches

Width Between Flats:

Between 0.865 inches and 0.877 inches

Grip Diameter:

Between 0.5610 inches and 0.5615 inches

Shank Unthreaded Hole Diameter:

0.141 inches and 0.151 inches all holes

Thread Diameter:

0.5625 inches

Grip Length:

Between 2.513 inches and 2.543 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

160000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.208 inches and 0.228 inches all holes

Material:

Iron alloy 660

Material Specification:

Ams5731 assn standard single material response or ams5732 assn standard single material response or ams5737 assn standard single material response or ams5853 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams-qq-p-416, type 2, class 2 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0