

View Online at <https://aerobasegroup.com/nsn/5306-01-594-9267>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.902 inches

**Fastener Length:**

Between 2.762 inches and 2.792 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.312 inches and 0.327 inches

**Width Between Flats:**

Between 0.928 inches and 0.940 inches

**Grip Diameter:**

Between 0.6230 inches and 0.6240 inches

**Shank Unthreaded Hole Diameter:**

0.141 inches and 0.151 inches all holes

**Thread Diameter:**

0.6250 inches

**Grip Length:**

Between 1.865 inches and 1.885 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

2.528 inches all holes

**Product Name:**

Bolt, tension, hex head, close tolerance, a286 cres, long thread, reduced major thread dia., self-locking and nonlocking, 160 ksi ftu

**Material:**

Steel

**Material Specification:**

Ams5781, 5732, 5737 or ams 5853 assn standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams-qq-p-416, type ii, class 2 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0