

View Online at <https://aerobasegroup.com/nsn/5306-01-596-2356>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.370 inches

**Fastener Length:**

3.120 inches

**Head Style:**

Hexagon

**Head Height:**

0.125 inches

**Width Between Flats:**

Between 0.430 inches and 0.439 inches

**Grip Diameter:**

Between 0.2485 inches and 0.2495 inches

**Thread Diameter:**

0.2475 inches

**Grip Length:**

2.750 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

6980 pounds per square inch

**Product Name:**

Bolt, sheer, hexagon head, close tolerance, short thread

**Special Features:**

Double sheer strength 10, 600lbs per minute, fatigue loading (pounds)3140hightension and 314 lowtension, heat treatment follows ams1759 for alloy steeland cres (corrosion resistance steel), includes a halogen free cetyl alcohol lubricant on allcres bolts both with/without the nas 4006 coating, cres-a286 (uns-566286) conforms to the chemistry of ams-h-81200

**Material:**

Stainless steel

**Thread Series Designator:**

Unjf

**Specification Data:**

Nas 2813thru 2830 national std/spec

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0