## NSN 5306-01-597-2728

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-597-2728 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.578 inches **Fastener Length:** Between 3.751 inches and 3.781 inches **Head Style:** Hexagon **Head Height:** Between 0.188 inches and 0.203 inches Width Between Flats: Between 0.554 inches and 0.564 inches **Grip Diameter:** Between 0.389 inches and 0.390 inches **Thread Diameter:** 0.375 inches **Grip Length:** Between 3.178 inches and 3.198 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch **Product Name:** Bolt, tension, hex head, close tolerance 160 ksi ftu Material: Steel comp 4140 or steel comp e4340 or steel comp 8740 **Material Specification:** Ams 6349 assn standard single material response or ams 6382 assn standard single material response or ams 6415 assn standard single material response or ams 6484 assn standard single material response or ams 6322 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Asm-qq-p-416, type ii, class 2 assn standard single treatment response **Thread Series Designator:** Unf Shelf Life: N/a

No

**Unit Of Measure:** 

Demilitarization:

## NSN 5306-01-597-2728

Shear Bolt - Page 2 of 2



Fiig:

A003b0