NSN 5306-01-597-5564

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-597-5564

View Online at https://aerobasegroup.com/nsn/5306-01-597-5564
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.408 inches
Fastener Length:
Between 1.793 inches and 1.823 inches
Head Style:
Hexagon extended washer
Head Height:
Between 0.195 inches and 0.215 inches
Width Between Flats:
Between 0.173 inches and 0.188 inches
Extended Washer Diameter:
Between 0.349 inches and 0.359 inches
Extended Washer Thickness:
Between 0.017 inches and 0.037 inches
Grip Diameter:
Between 0.189 inches and 0.190 inches
End Application:
1520-01-492-6324 helicopter, utility
Thread Diameter:
0.190 inches
Grip Length:
Between 1.365 inches and 1.385 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
7100 pounds per square inch
Product Name:
Bolt, tension
Material:
Nickel alloy
Material Specification:
Ams 5662 assn standard single material response or asm 5663 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35, type ii, class 2 federal specification single treatment response
Thread Series Designator:

Unjf

NSN 5306-01-597-5564

Shear Bolt - Page 2 of 2



	Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0