

View Online at <https://aerobasegroup.com/nsn/5306-01-598-9349>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.412 inches

**Fastener Length:**

Between 1.460 inches and 1.490 inches

**Head Style:**

Double hexagon extended washer

**Head Height:**

Between 0.290 inches and 0.310 inches

**Width Between Flats:**

Between 0.304 inches and 0.313 inches

**Extended Washer Diameter:**

Between 0.428 inches and 0.438 inches

**Extended Washer Thickness:**

Between 0.428 inches and 0.430 inches

**Grip Diameter:**

Between 0.249 inches and 0.250 inches

**End Application:**

Global hawk

**Thread Diameter:**

0.250 inches

**Grip Length:**

1.063 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Product Name:**

Bolt, tension, extrnal wrenching

**Material:**

Stainless steel

**Material Specification:**

Ams 5853 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Ams-qq-p-35 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0