NSN 5306-01-599-4325

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-599-4325

view offilite at https://defobasegroup.com/hish/5500-01-555-4525
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.425 inches
Fastener Length:
Between 0.472 inches and 0.502 inches
Head Style:
Dished hexagon
Head Height:
Between 0.125 inches and 0.140 inches
Width Between Flats:
Between 0.429 inches and 0.439 inches
Hole Diameter:
0.046 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
End Application:
Various cs
Thread Diameter:
0.250 inches
Grip Length:
Between 0.052 inches and 0.072 inches
Hole Quantity:
3
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Hole Configuration Style:
Hexagon corners
Material:
Steel comp 4140 or steel comp 4340 or steel comp 8740
Material Specification:
Ams6349 assn standard 1st material response or ams6382 assn standard 1st material response or ams6415 assn standard 2nd material
response or ams6484 assn standard 2nd material response or ams6322 assn standard 3rd material response
Surface Treatment:
Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

NSN 5306-01-599-4325

Shear Bolt - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0