## NSN 5306-01-599-4333

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-599-4333

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.578 inches
Fastener Length:
Between 0.625 inches and 0.655 inches
Head Style:
Dished hexagon
Head Height:
Between 0.188 inches and 0.203 inches
Width Between Flats:
Between 0.554 inches and 0.564 inches
Hole Diameter:
0.07 inches
Grip Diameter:
Between 0.311 inches and 0.312 inches
End Application:
Various c5
Thread Diameter:
0.375 inches
Grip Length:
Between 0.052 inches and 0.072 inches
Hole Quantity:
3
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Hole Configuration Style:
Hexagon corners
Material:
Steel comp 4140 or steel comp 4340 or steel comp 8740
Material Specification:
Ams6349 assn standard 1st material response or ams6382 assn standard 1st material response or ams6415 assn standard 2nd material
response or ams6484 assn standard 2nd material response or ams6322 assn standard 3rd material response
Surface Treatment:

Cadmium

**Surface Treatment Specification:** 

Qq-p-416, type 2, cl 2 federal specification single treatment response

## NSN 5306-01-599-4333

Shear Bolt - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0