## NSN 5306-01-599-4569

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-599-4569

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.469 inches
Fastener Length:
1.344 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.4645 inches and 0.4739 inches
Hole Diameter:
0.076 inches
Grip Diameter:
Between 0.3271 inches and 0.3276 inches
Thread Diameter:
0.312 inches
Grip Length:
0.875 inches
Hole Quantity:
1
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi): 24
24
24 Hole Configuration Style:
24 Hole Configuration Style: Round
24 Hole Configuration Style: Round Countersink Angle:
24 Hole Configuration Style: Round Countersink Angle: Between 90.0 degrees and 101.0 degrees
24 Hole Configuration Style: Round Countersink Angle: Between 90.0 degrees and 101.0 degrees Material:
24 Hole Configuration Style: Round Countersink Angle: Between 90.0 degrees and 101.0 degrees Material: Nickel alloy 718
24 Hole Configuration Style: Round Countersink Angle: Between 90.0 degrees and 101.0 degrees Material: Nickel alloy 718 Material Specification:
24 Hole Configuration Style: Round Countersink Angle: Between 90.0 degrees and 101.0 degrees Material: Nickel alloy 718 Material Specification: Ams5662 assn standard single material response
24 Hole Configuration Style: Round Countersink Angle: Between 90.0 degrees and 101.0 degrees Material: Nickel alloy 718 Material Specification: Ams5662 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:
24 Hole Configuration Style: Round Countersink Angle: Between 90.0 degrees and 101.0 degrees Material: Nickel alloy 718 Material Specification: Ams5662 assn standard single material response Surface Treatment: Passivate
24 Hole Configuration Style: Round Countersink Angle: Between 90.0 degrees and 101.0 degrees Material: Nickel alloy 718 Material Specification: Ams5662 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification:
24 Hole Configuration Style: Round Countersink Angle: Between 90.0 degrees and 101.0 degrees Material: Nickel alloy 718 Material Specification: Ams5662 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Mil-I-87132, type 1, grade b military specification single treatment response

N/a

## NSN 5306-01-599-4569

Close Tolerance Bolt - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-I-87132 spec.

