NSN 5306-01-600-0613

Machine Bolt - Page 1 of 2

Thread Class:

За



View Online at https://aerobasegroup.com/nsn/5306-01-600-0613

| Thread Direction: |
|---|
| Right-hand |
| Thread Length: |
| 0.687 inches |
| Fastener Length: |
| 0.687 inches |
| Head Style: |
| Double hexagon w/hole |
| Head Height: |
| 0.430 inches |
| Width Between Flats: |
| Between 0.637 inches and 0.651 inches |
| Extended Washer Diameter: |
| 0.823 inches |
| Extended Washer Thickness: |
| 0.123 inches |
| Hole Diameter: |
| Between 0.050 inches and 0.060 inches |
| Thread Diameter: |
| 0.500 inches |
| Hole Quantity: |
| 4 |
| Hole Type: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 20 |
| Min. Tensile Strength (psi): |
| 180000 pounds per square inch |
| Hole Configuration Style: |
| Double hexagon longitudinal hole |
| Material: |
| Nickel alloy 718 |
| Material Specification: |
| Ams 5662 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Ams2700, method 1, type 2 or type 8 assn standard single treatment response |
| |
| Thread Series Designator: |
| Thread Series Designator: Unjf |

NSN 5306-01-600-0613

Machine Bolt - Page 2 of 2



| | | ife: | |
|--|--|------|--|
| | | | |
| | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0