

View Online at <https://aerobasegroup.com/nsn/5306-01-600-1041>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.420 inches and 0.460 inches

**Fastener Length:**

Between 0.680 inches and 0.700 inches

**Head Style:**

Double hexagon w/hole

**Head Inside Diameter:**

Between 0.095 inches and 0.135 inches

**Head Height:**

Between 0.255 inches and 0.275 inches

**Width Between Flats:**

Between 0.235 inches and 0.250 inches

**Extended Washer Diameter:**

Between 0.340 inches and 0.350 inches

**Extended Washer Thickness:**

Between 0.045 inches and 0.065 inches

**Grip Diameter:**

Between 0.189 inches and 0.190 inches

**End Application:**

Stryker

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.240 inches and 0.260 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Product Name:**

Bolt, tension, external wrenching, flanged, 12-point

**Material:**

Steel

**Material Specification:**

Mil-s-5626 military specification single material response or mil-s-5000 military specification single material response or mil-s-6049 military specification single material response

**Surface Treatment:**

Zinc

**Surface Treatment Specification:**

Astm b633, fe/zn8, type 1 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.