

View Online at <https://aerobasegroup.com/nsn/5306-01-600-1041>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.420 inches and 0.460 inches

Fastener Length:

Between 0.680 inches and 0.700 inches

Head Style:

Double hexagon w/hole

Head Inside Diameter:

Between 0.095 inches and 0.135 inches

Head Height:

Between 0.255 inches and 0.275 inches

Width Between Flats:

Between 0.235 inches and 0.250 inches

Extended Washer Diameter:

Between 0.340 inches and 0.350 inches

Extended Washer Thickness:

Between 0.045 inches and 0.065 inches

Grip Diameter:

Between 0.189 inches and 0.190 inches

End Application:

Stryker

Thread Diameter:

0.190 inches

Grip Length:

Between 0.240 inches and 0.260 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

180000 pounds per square inch

Product Name:

Bolt, tension, external wrenching, flanged, 12-point

Material:

Steel

Material Specification:

Mil-s-5626 military specification single material response or mil-s-5000 military specification single material response or mil-s-6049 military specification single material response

Surface Treatment:

Zinc

Surface Treatment Specification:

Astm b633, fe/zn8, type 1 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.