## NSN 5306-01-600-6060

Internal Wrenching Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-01-600-6060

| Thread Class:       |  |
|---------------------|--|
| 3a                  |  |
| Thread Direction    | n:   |
| Right-hand          |  |
| Thread Length:      |  |
| 1.750 inches        |  |
| Fastener Length     | 1:   |
| Between 2.090 ir    | iches and 2.120 inches   |
| Head Style:         |  |
| Hexagon             |  |
| Head Height:        |  |
| Between 0.105 ir    | iches and 0.120 inches   |
| Width Between       | Flats:   |
| Between 0.306 ir    | iches and 0.313 inches   |
| Internal Drive St   | yle:   |
| Tri-wing recess     |  |
| Thread Diamete      | r:   |
| 0.190 inches        |  |
| Thready Qty Per     | Inch (tpi):  |
| 32                  |  |
| Min. Tensile Str    | ength (psi):   |
| 160000 pounds p     | per square inch  |
| Product Name:       |  |
| Screw, hex head     | l, tri-wing recess, 6al-4v titanium alloy, full thread, nonlocking           |
| Special Feature     | S:   |
| Airworthy certifica | ated item supplied w   |
| Material:           |  |
| Titanium alloy un   | s r56400   |
| Material Specifie   | cation:  |
| Ams4928 assn s      | andard 1st material response and ams4967 assn standard 1st material response |
| Thread Series D     | esignator:   |
| Unf                 |  |
| Specification Da    | ata:   |
| 80205-nas6100 t     | hrough 6103 professional/industrial association standard                     |
| Shelf Life:         |  |
| N/a                 |  |
| Unit Of Measure     | :  |
|                     |  |
| Demilitarization    | :  |
| No                  |  |
| Fiig:               |  |
| A003b0              |  |