## NSN 5306-01-602-9594

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-602-9594

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
1.173 inches
Fastener Length:
1.448 inches
Head Style:
Spline extended washer
Head Height:
0.600 inches
Extended Washer Diameter:
Between 1.384 inches and 1.394 inches
Extended Washer Thickness:
Between 0.098 inches and 0.118 inches
Grip Diameter:
Between 0.748 inches and 0.749 inches
Head Minor Diameter:
Between 0.797 inches and 0.812 inches
End Application:
F-22 raptor
Thread Diameter:
0.7500 inches
Grip Length:
0.250 inches
Features Provided:
Dry film lubricant
Thready Qty Per Inch (tpi):
16
Min. Tensile Strength (psi):
220 pounds per square inch
Surface Finish:
32.0 microinches
Special Features:
Double shear strength109857
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response or ams 5663 assn standard single material response
Surface Treatment:

Passivate

## NSN 5306-01-602-9594

Shear Bolt - Page 2 of 2



Qq-p-35 federal standard single treatment response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0