

View Online at <https://aerobasegroup.com/nsn/5306-01-603-7859>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.626 inches

**Fastener Length:**

2.751 inches

**Head Style:**

Hexagon

**Head Height:**

0.312 inches

**Width Between Flats:**

Between 0.928 inches and 0.940 inches

**Grip Diameter:**

Between 0.6542 inches and 0.6552 inches

**Point Length:**

0.068 inches

**Point Diameter:**

Between 0.6120 inches and 0.6180 inches

**Point Style:**

Flat

**End Application:**

5935-01-118-9183

**Thread Diameter:**

0.625 inches

**Grip Length:**

2.1875 inches

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Chamfer Angle:**

Between 10.0 degrees and 20.0 degrees

**Product Name:**

Bolt, tension, hex head, close tolerance

**Material:**

Steel comp 4140 or steel comp 4340 or steel comp 8740

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Ams-qq-p-416, type ii, class 2 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A003b0