

View Online at <https://aerobasegroup.com/nsn/5306-01-604-2876>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.902 inches

Fastener Length:

3.34 inches

Head Style:

Dished hexagon

Head Height:

Between 0.312 inches and 0.327 inches

Width Between Flats:

Between 0.928 inches and 0.940 inches

Grip Diameter:

Between 0.623 inches and 0.624 inches

End Application:

Ac130h acft

Thread Diameter:

0.625 inches

Grip Length:

Between 2.428 inches and 2.448 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

160000 pounds per square inch

Product Name:

Bolt, tension, hex head, close tolerance

Special Features:

Embrittlement requirement per nas4002

Material:

Steel comp 4140 or steel comp 4340 or steel comp 8740

Material Specification:

Ams6349 assn standard single material response or ams6382 assn standard single material response or ams6415 assn standard single material response or ams6484 assn standard single material response or ams6322 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2, class 2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0