NSN 5306-01-604-2876

Shear Bolt - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5306-01-604-2876 |
|--|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.902 inches |
| Fastener Length: |
| 3.34 inches |
| Head Style: |
| Dished hexagon |
| Head Height: |
| Between 0.312 inches and 0.327 inches |
| Width Between Flats: |
| Between 0.928 inches and 0.940 inches |
| Grip Diameter: |
| Between 0.623 inches and 0.624 inches |
| End Application: |
| Ac130h acft |
| Thread Diameter: |
| 0.625 inches |
| Grip Length: |
| Between 2.428 inches and 2.448 inches |
| Thready Qty Per Inch (tpi): |
| 18 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Product Name: |
| Bolt, tension, hex head, close tollerance |
| Special Features: |
| Embrittlement requirement per nas4002 |
| Material: |
| Steel comp 4140 or steel comp 4340 or steel comp 8740 |
| Material Specification: |
| Ams6349 assn standard single material response or ams6382 assn standard single material response or ams6415 assn standard single |
| material response or ams6484 assn standard single material response or ams6322 assn standard single material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416, type 2, class 2 federal specification single treatment response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |

N/a

NSN 5306-01-604-2876

Shear Bolt - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|-----|-----|------|
| In | 18 | <i>(</i>)+ | МЛО | 201 | ure: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A003b0