NSN 5306-01-604-3228

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-604-3228

material response or ams5853 assn standard single material response

Surface Treatment:

Passivate

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.438 inches
Fastener Length:
Between 1.049 inches and 1.079 inches
Head Style:
Dished hexagon
Head Height:
Between 0.156 inches and 0.171 inches
Width Between Flats:
Between 0.492 inches and 0.502 inches
Hole Diameter:
Between 0.07 inches and 0.08 inches
Grip Diameter:
Between 0.3115 inches and 0.3120 inches
End Application:
T38 aircraft
Thread Diameter:
0.3125 inches
Grip Length:
Between 0.611 inches and 0.641 inches
Hole Quantity:
3
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Hole Configuration Style:
Double hexagon flats
Product Name:
Bolt, tension, hex head, close tolerance
Material:
Iron alloy 660
Material Specification:
Ams5731 assn standard single material response or ams5732 assn standard single material response or ams5737 assn standard single

NSN 5306-01-604-3228

Shear Bolt - Page 2 of 2



	Surface	Treatment	Specification:
--	---------	------------------	----------------

Ams2700, method 1, type 2 or type 8, class 1 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0