## NSN 5306-01-605-9255

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-605-9255

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.840 inches
Fastener Length:
3.465 inches
Head Style:
Hexagon
Head Height:
0.281 inches
Width Between Flats:
Between 0.865 inches and 0.877 inches
Hole Diameter:
0.070 inches
Grip Diameter:
Between 0.5610 inches and 0.5615 inches
Shank Unthreaded Hole Diameter:
0.141 inches fastener
Thread Diameter:
0.562 inches
Grip Length:
2.625 inches
Hole Quantity:
3 and 1
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
18
Min. Tensile Strength (psi):
160000 pounds per square inch
Hole Configuration Style:
Hexagon corners
Distance From Head Largest Bearing Surface To Shank Hole Center:
3.247 inches fastener
Material:
Iron alloy 660
Material Specification:
Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single

Passivate

**Surface Treatment:** 

material response or ams 5853 assn standard single material response

## NSN 5306-01-605-9255

Shear Bolt - Page 2 of 2



Ams 2700, method 1, type 2 or 8, class 1 assn standard single treatment response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0