NSN 5306-01-605-9885

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-605-9885

Thread	Class:

3a

Thread Direction:

Right-hand

Thread Length:

1.036 inches

Fastener Length:

3.3485 inches

Head Style:

Double hexagon w/hole

Head Height:

0.711 inches

Width Between Flats:

0.8125 inches

Extended Washer Diameter:

Between 1.22 inches and 1.23 inches

Extended Washer Thickness:

0.178 inches

Grip Diameter:

Between 0.7480 inches and 0.7490 inches

End Application:

C130 acft

Thread Diameter:

0.75 inches

Grip Length:

2.3125 inches

Thready Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

200000 pounds per square inch

Surface Finish:

125.0 microinches

Product Name:

Bolt, tension, steel, 180 ksi ftu, 450degree f, 12 point, external wrenching flanged

Material:

Steel comp 4140

Material Specification:

Mil-s-5626, mil-s-5000, mil-s-6049 or mil-s-8503 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416 type ii, class 2 federal specification single treatment response

NSN 5306-01-605-9885

Shear Bolt - Page 2 of 2

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.

