NSN 5306-01-605-9888

Shear Bolt - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/5306-01-605-9888

3a
Thread Direction:
Right-hand
Thread Length:
1.036 inches
Fastener Length:
3.8485 inches
Head Style:
Double hexagon w/hole
Head Height:
0.711 inches
Width Between Flats:
0.8125 inches
Extended Washer Diameter:
Between 1.22 inches and 1.23 inches
Extended Washer Thickness:
0.178 inches
Grip Diameter:
Between 0.7480 inches and 0.7490 inches
End Application:
C130 acft
Thread Diameter:
0.75 inches
Grip Length:
2.8125 inches
Thready Qty Per Inch (tpi):
16
Min. Tensile Strength (psi):
200000 pounds per square inch
Surface Finish:
125.0 microinches
Product Name:
Bolt, tension, steel, external wrenching, flanged, 12-point, 180ksi ftu, 450degree f
Material:
Steel comp 4140
Material Specification:
Mil-s-5626, mil-s-5000, mil-s-6049 or mil-s-8503 military specification single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416 type ii, class 2 federal specification single treatment response

NSN 5306-01-605-9888

Shear Bolt - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

Mil-std (military Standard):

Mil-s-5626 spec.