NSN 5306-01-606-5244

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-606-5244

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.763 inches
Fastener Length:
3.913 inches
Head Style:
Spline extended washer
Head Height:
0.393 inches
Extended Washer Diameter:
Between 0.807 inches and 0.817 inches
Extended Washer Thickness:
Between 0.053 inches and 0.073 inches
Hole Diameter:
0.066 inches
Grip Diameter:
Between 0.4360 inches and 0.4370 inches
Head Minor Diameter:
Between 0.486 inches and 0.500 inches
Thread Diameter:
0.437 inches
Grip Length:
3.125 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
220000 pounds per square inch
Hole Configuration Style:
Spline
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response or ams 5663 assn standard single material response
Surface Treatment:

Passivate

NSN 5306-01-606-5244

Shear Bolt - Page 2 of 2



Surface	Treatment	Specif	ication:
Juliace	HEALINGIL	Opecii	ıcalıcı.

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0