## NSN 5306-01-608-4484

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-608-4484

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.408 inches
Fastener Length:
2.058 inches
Head Style:
Spline extended washer
Head Height:
Between 0.195 inches and 0.215 inches
Extended Washer Diameter:
Between 0.349 inches and 0.359 inches
Extended Washer Thickness:
Between 0.017 inches and 0.037 inches
Grip Diameter:
Between 0.1885 inches and 0.1895 inches
Single Shear Strength:
3550 pounds per square inch
Head Minor Diameter:
Between 0.173 inches and 0.188 inches
End Application:
Uh-60m crew chief/gunner w/baps
Thread Diameter:
0.190 inches
Grip Length:
Between 1.615 inches and 1.635 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
220000 pounds per square inch
Product Name:
Bolt, tension, nickel alloy 718, external wrenching
Special Features:
Surface finish iaw ansi/asme b46.1
Material:
Nickel alloy 718
Material Specification:
Ams5662 or ams5663 or ams5962 assn standard single material response
Surface Treatment:

Passivate

## NSN 5306-01-608-4484

Shear Bolt - Page 2 of 2



Ams-qq-p-35 assn standard single treatment response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0