## NSN 5306-01-608-5744

Close Tolerance Bolt - Page 1 of 2





## **Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.563 inches and 0.593 inches Fastener Length: Between 0.803 inches and 0.853 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.5504 inches and 0.5604 inches **Head Height:** 0.075 inches Hole Diameter: 0.106 inches **Grip Diameter:** Between 0.3896 inches and 0.3901 inches **End Application:** F/a-18 e/f **Thread Diameter:** 0.3750 inches Grip Length: 0.250 inches Hole Type: Drilled Thready Qty Per Inch (tpi): 24 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Bolt, close tolerance Material: Nickel alloy 718 **Material Specification:** Ms 5662 national std/spec single material response **Surface Treatment Specification:** Sme b46.1 national std/spec single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

## NSN 5306-01-608-5744

Close Tolerance Bolt - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

Yes - demil/mli

Fiig:

A003b0

