## NSN 5306-01-608-6146

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-608-6146 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.370 inches **Fastener Length:** Between 0.605 inches and 0.635 inches **Head Style:** Fillister countersunk **Head Diameter:** 0.397 inches **Head Height:** 0.014 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Point Diameter:** Between 0.241 inches and 0.244 inches **Point Style:** Flat **End Application:** Pylon **Thread Diameter:** 0.2500 inches **Grip Length:** Between 0.240 inches and 0.260 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Screw, close tolerance **Special Features:** Nas document states bolt, 100 degree reduced head close Material: Stainless steel **Surface Treatment:** Aluminum

**Thread Series Designator:** Unjf

## NSN 5306-01-608-6146

Close Tolerance Bolt - Page 2 of 2



Spec	ifica	ation	Data:
------	-------	-------	-------

80205-nas8704a4 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0