

View Online at <https://aerobasegroup.com/nsn/5306-01-608-7390>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.619 inches

Fastener Length:

Between 0.854 inches and 0.884 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.378 inches and 0.398 inches

Width Between Flats:

Between 0.430 inches and 0.439 inches

Extended Washer Diameter:

Between 0.639 inches and 0.649 inches

Extended Washer Thickness:

Between 0.081 inches and 0.101 inches

Hole Diameter:

Between 0.050 inches and 0.060 inches

Grip Diameter:

0.3750 inches

End Application:

Dragonspear

Thread Diameter:

0.3750 inches

Grip Length:

Between 0.240 inches and 0.260 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

17100 pounds per square inch

Hardness Rating:

39.0 rockwell c

Hole Configuration Style:

Double hexagon longitudinal hole

Product Name:

Bolt, shear

Special Features:

Bolt, tension, alloy steel, twelve point, external wench

Material:

Steel

Material Specification:

Ams6382 assn standard 1st material response or ams6415 assn standard 2nd material response or ams6484 assn standard 3rd material response or ams6322 assn standard 4th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Nas672 assn standard single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas626h4 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0