## NSN 5306-01-608-7974

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-608-7974

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.528 inches
Fastener Length:
2.466 inches
Head Style:
Hexagon
Head Height:
0.250 inches
Width Between Flats:
Between 0.741 inches and 0.752 inches
Hole Diameter:
Between 0.070 inches and 0.080 inches
Grip Diameter:
Between 0.4985 inches and 0.4995 inches
End Application:
Rq-4a
Thread Diameter:
0.5000 inches
Grip Length:
1.938 inches
Hole Quantity:
3
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
160000 pounds per square inch
Hole Configuration Style:
Hexagon corners
Surface Finish:
32.0 microinches bearing surface of head
Product Name:
Bolt, tension, hex head, close tolerance
Material:
Steel comp 4140 or steel comp 4340 or steel comp 8740
Surface Treatment:
Cadmium

## NSN 5306-01-608-7974

Shear Bolt - Page 2 of 2



Surface Treatment S	pecification:
---------------------	---------------

Qq-p-416, type ii, class 2 federal standard single treatment response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0