

View Online at <https://aerobasegroup.com/nsn/5306-01-611-3532>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.637 inches

Fastener Length:

Between 0.754 inches and 0.784 inches

Head Style:

Hexagon

Head Height:

Between 0.312 inches and 0.327 inches

Width Between Flats:

Between 0.928 inches and 0.940 inches

Grip Diameter:

Between 0.6230 inches and 0.6240 inches

End Application:

Various c5 918s

Thread Diameter:

0.6250 inches

Grip Length:

Between 0.117 inches and 0.147 inches

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

140000 pounds per square inch

Product Name:

Hex head, short thread, close tol, alloy steel

Special Features:

Drilled shank

Material:

Steel comp 4340 or steel comp 8740

Material Specification:

Ams6415 assn standard 1st material response or ams6484 assn standard 2nd material response or ams6322 assn standard 3rd material response or mil-s-6049 military specification single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Ams-qq-+0416 type ii class 2 and bps-f-69 assn standard single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-bacb30nf10d132 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6049 spec.