NSN 5306-01-613-3735

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-613-3735

Thread Class:

Thread Direction: Right-hand Thread Length: 0.370 inches Fastener Length: 2.428 inches Head Style: Dished hexagon Head Height: 0.125 inches Width Between Flats: Between 0.429 inches and 0.439 inches Grip Diameter: Between 0.2485 inches and 0.2495 inches End Application: Kc-135 acft Thread Diameter: 0.250 inches Grip Length:
Thread Length: 0.370 inches Fastener Length: 2.428 inches Head Style: Dished hexagon Head Height: 0.125 inches Width Between Flats: Between 0.429 inches and 0.439 inches Grip Diameter: Between 0.2485 inches and 0.2495 inches End Application: Kc-135 acft Thread Diameter: 0.250 inches Grip Length:
0.370 inches Fastener Length: 2.428 inches Head Style: Dished hexagon Head Height: 0.125 inches Width Between Flats: Between 0.429 inches and 0.439 inches Grip Diameter: Between 0.2485 inches and 0.2495 inches End Application: Kc-135 acft Thread Diameter: 0.250 inches Grip Length:
Fastener Length: 2.428 inches Head Style: Dished hexagon Head Height: 0.125 inches Width Between Flats: Between 0.429 inches and 0.439 inches Grip Diameter: Between 0.2485 inches and 0.2495 inches End Application: Kc-135 acft Thread Diameter: 0.250 inches Grip Length:
2.428 inches Head Style: Dished hexagon Head Height: 0.125 inches Width Between Flats: Between 0.429 inches and 0.439 inches Grip Diameter: Between 0.2485 inches and 0.2495 inches End Application: Kc-135 acft Thread Diameter: 0.250 inches Grip Length:
Head Style: Dished hexagon Head Height: 0.125 inches Width Between Flats: Between 0.429 inches and 0.439 inches Grip Diameter: Between 0.2485 inches and 0.2495 inches End Application: Kc-135 acft Thread Diameter: 0.250 inches Grip Length:
Dished hexagon Head Height: 0.125 inches Width Between Flats: Between 0.429 inches and 0.439 inches Grip Diameter: Between 0.2485 inches and 0.2495 inches End Application: Kc-135 acft Thread Diameter: 0.250 inches Grip Length:
Head Height: 0.125 inches Width Between Flats: Between 0.429 inches and 0.439 inches Grip Diameter: Between 0.2485 inches and 0.2495 inches End Application: Kc-135 acft Thread Diameter: 0.250 inches Grip Length:
0.125 inches Width Between Flats: Between 0.429 inches and 0.439 inches Grip Diameter: Between 0.2485 inches and 0.2495 inches End Application: Kc-135 acft Thread Diameter: 0.250 inches Grip Length:
Width Between Flats: Between 0.429 inches and 0.439 inches Grip Diameter: Between 0.2485 inches and 0.2495 inches End Application: Kc-135 acft Thread Diameter: 0.250 inches Grip Length:
Between 0.429 inches and 0.439 inches Grip Diameter: Between 0.2485 inches and 0.2495 inches End Application: Kc-135 acft Thread Diameter: 0.250 inches Grip Length:
Grip Diameter: Between 0.2485 inches and 0.2495 inches End Application: Kc-135 acft Thread Diameter: 0.250 inches Grip Length:
Between 0.2485 inches and 0.2495 inches End Application: Kc-135 acft Thread Diameter: 0.250 inches Grip Length:
End Application: Kc-135 acft Thread Diameter: 0.250 inches Grip Length:
Kc-135 acft Thread Diameter: 0.250 inches Grip Length:
Thread Diameter: 0.250 inches Grip Length:
0.250 inches Grip Length:
Grip Length:
0.050 1
2.058 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Product Name:
Hex head bolt
Material:
Titanium alloy uns r56400
Material Specification:
Ams4928 assn standard single material response
Surface Treatment:
Aluminum
Thread Series Designator:
Unjf
Unjf Specification Data:
•
Specification Data:
Specification Data: 80205-nas6404 professional/industrial association standard

--

NSN 5306-01-613-3735

Shear Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0