NSN 5306-01-613-8967



Machine Bolt - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5306-01-613-8967 **Thread Direction:** Right-hand Thread Length: Between 0.75 inches and 0.95 inches **Fastener Length:** Between 1.1875 inches and 1.3875 inches **Head Style:** Countersunk cylindrical convex **Locking Feature:** Slotted locking feature **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Head Major Diameter:** Between 0.2937 inches and 0.3011 inches **End Application:** Frame instl-entry door panel sta 348.2 **Thread Diameter:** 0.1900 inches **Grip Length:** Between 0.4325 inches and 0.4425 inches **Countersink Angle:** 100.0 degrees **Product Name:** Bolt **Special Features:** Bolt has a shear strength of 95000psi. Finish is designated by yellow dye or paint on a portion of the pintail. Threaded portion breaks off after bolt is inserted. Bolt is kept in place by locking grooves. Maximum service temp is 250 degrees f. Material: Titanium alloy uns r56400 **Material Specification:** Ams4928 assn standard single material response or ams4967 assn standard single material response **Surface Treatment:** Aluminum **Surface Treatment Specification:** Bms10-85, type 1, class a mfr ref single treatment response Shelf Life: N/a **Unit Of Measure:**

Fiig: A003b0

No

Demilitarization: