NSN 5306-01-614-1459

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-614-1459
Thread Class:
3
Thread Direction:
Right-hand
Thread Length:
Between 0.569 inches and 0.619 inches
Fastener Length:
Between 3.367 inches and 3.397 inches
Head Style:
Dished hexagon
Head Height:
Between 0.218 inches and 0.296 inches
Width Between Flats:
Between 0.865 inches and 0.877 inches
Grip Diameter:
Between 0.5605 inches and 0.5615 inches
Thread Diameter:
0.562 inches
Grip Length:
Between 2.778 inches and 2.798 inches
Thready Qty Per Inch (tpi):
18
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c and 40.0 rockwell c
Surface Finish:
32.0 microinches threads
Material:
Steel comp e4340 or steel comp 8740
Material Specification:
Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 1st material response or ams6322 assn standard
2nd material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2 class 2 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:

Shelf Life:

80205-nas6209 professional/industrial association standard

N/a

NSN 5306-01-614-1459

Shear Bolt - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.