## NSN 5306-01-614-1636

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-614-1636

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
1.399 inches
Fastener Length:
Between 7.634 inches and 7.664 inches
Head Style:
Double hexagon w/hole
Head Height:
0.712 inches
Width Between Flats:
Between 1.052 inches and 1.064 inches
Extended Washer Diameter:
Between 1.580 inches and 1.590 inches
Extended Washer Thickness:
0.240 inches
Grip Diameter:
Between 0.9980 inches and 0.9990 inches
End Application:
C-5m aircraft
Thread Diameter:
1.000 inches
Grip Length:
Between 6.240 inches and 6.260 inches
Features Provided:
Cetyl alcohol lubricant
Thready Qty Per Inch (tpi):
12
Min. Tensile Strength (psi):
260000 pounds per square inch
Product Name:
Bolt-tension, external wrenching, 12-point, light weight, 260 ksi ftu steel, 900 deg. F
Special Features:
Temp. Range -65 deg. F. To 900 deg. F.
Material:
Steel comp h11
Material Specification:
Stsbs003, cage 98897 mfr ref single material response
Surface Treatment:
Nickel and cadmium

## NSN 5306-01-614-1636

Shear Bolt - Page 2 of 2



Stsbs003, cage 98897 mfr ref all treatment responses

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0