

View Online at <https://aerobasegroup.com/nsn/5306-01-614-1636>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

1.399 inches

**Fastener Length:**

Between 7.634 inches and 7.664 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

0.712 inches

**Width Between Flats:**

Between 1.052 inches and 1.064 inches

**Extended Washer Diameter:**

Between 1.580 inches and 1.590 inches

**Extended Washer Thickness:**

0.240 inches

**Grip Diameter:**

Between 0.9980 inches and 0.9990 inches

**End Application:**

C-5m aircraft

**Thread Diameter:**

1.000 inches

**Grip Length:**

Between 6.240 inches and 6.260 inches

**Features Provided:**

Cetyl alcohol lubricant

**Thready Qty Per Inch (tpi):**

12

**Min. Tensile Strength (psi):**

260000 pounds per square inch

**Product Name:**

Bolt-tension, external wrenching, 12-point, light weight, 260 ksi ftu steel, 900 deg. F

**Special Features:**

Temp. Range -65 deg. F. To 900 deg. F.

**Material:**

Steel comp h11

**Material Specification:**

Stsbs003, cage 98897 mfr ref single material response

**Surface Treatment:**

Nickel and cadmium

**Surface Treatment Specification:**

Stsbs003, cage 98897 mfr ref all treatment responses

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0