NSN 5306-01-615-0612

Shear Bolt - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5306-01-615-0612
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
1.041 inches
Fastener Length:
Between 5.151 inches and 5.181 inches
Head Style:
Hexagon
Head Height:
Between 0.375 inches and 0.390 inches
Width Between Flats:
Between 1.052 inches and 1.065 inches
Grip Diameter:
Between 0.7480 inches and 0.7490 inches
End Application:
1520-01-355-8250
Thread Diameter:
0.7500 inches
Grip Length:
Between 4.115 inches and 4.135 inches
Thready Qty Per Inch (tpi):
16
Min. Tensile Strength (psi):
160000 pounds per square inch
Product Name:
Bolt, shear
Material:
Steel comp 4140 or steel comp 4340 or steel comp 8740
Material Specification:
Ams6349 assn standard 1st material response or ams6382 assn standard 2nd material response or ams6415 assn standard 3rd material
response or ams6484 assn standard 4th material response or ams6322 assn standard 5th material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Ams-qq-p-416, type ii, class 2 assn standard single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas6612-66 professional/industrial association standard
Shelf Life:

N/a

NSN 5306-01-615-0612

Shear Bolt - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0