

View Online at <https://aerobasegroup.com/nsn/5306-01-615-1387>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.707 inches

**Fastener Length:**

Between 3.442 inches and 3.472 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

0.388 inches

**Width Between Flats:**

Between 0.430 inches and 0.439 inches

**Extended Washer Diameter:**

Between 0.639 inches and 0.649 inches

**Extended Washer Thickness:**

0.091 inches

**Grip Diameter:**

Between 0.3735 inches and 0.3745 inches

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 2.74 inches and 2.76 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

260000 pounds per square inch

**Product Name:**

Bolt, tension, double hexagon, mp35n material, 260 ksi

**Material:**

Nickel alloy

**Material Specification:**

Ams 5758 assn standard single material response and ams 5844 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Ams-qq-p-35, type 2 assn standard single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0