NSN 5306-01-615-1390

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-01-615-1390 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.707 inches **Fastener Length:** Between 4.255 inches and 4.285 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.388 inches Width Between Flats: Between 0.430 inches and 0.439 inches **Extended Washer Diameter:** Between 0.639 inches and 0.649 inches **Extended Washer Thickness:** 0.091 inches **Grip Diameter:** Between 0.3735 inches and 0.3745 inches **Thread Diameter:** 0.375 inches **Grip Length:** Between 3.553 inches and 3.573 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 260000 pounds per square inch **Product Name:** Bolt, tension, double hexagon, mp35n material, 260 ksi Material:

Nickel alloy

Material Specification:

Ams 5758 assn standard single material response and ams 5844 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Ams-qq-p-35, type 2 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

NSN 5306-01-615-1390 Machine Bolt - Page 2 of 2



			ıre:

Demilitarization:

No

Fiig:

A003b0