

View Online at <https://aerobasegroup.com/nsn/5306-01-616-3918>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.740 inches and 0.760 inches

Fastener Length:

Between 0.740 inches and 0.760 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.365 inches and 0.385 inches

Width Between Flats:

0.3750 inches

Extended Washer Diameter:

Between 0.490 inches and 0.510 inches

Extended Washer Thickness:

Between 0.070 inches and 0.080 inches

Hole Diameter:

Between 0.060 inches and 0.080 inches

End Application:

Mk 7 mod 1 ra

Thread Diameter:

0.3125 inches

Hole Quantity:

4

Hole Type:

Drilled

Features Provided:

Dry film lubricant

Thready Qty Per Inch (tpi):

24

Hole Configuration Style:

Double hexagon flats

Surface Finish:

125.0 microinches threads

Product Name:

Bolt, machine

Special Features:

Bolt is altered from ms9171-08 with solid film lubricant 5191127; lubricant applied to all surfaces except omit from threads

Material:

Steel

Material Specification:

Low alloy steel per ams632 (uns g87400) national std/spec single material response

Surface Treatment:

Black chemical finish

Surface Treatment Specification:

Black oxide per ams2485 national std/spec single treatment response

Thread Series Designator:

Unf

Specification Data:

81343-sae as91711 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0