

View Online at <https://aerobasegroup.com/nsn/5306-01-616-9556>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.454 inches

**Fastener Length:**

Between 1.627 inches and 1.657 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.188 inches and 0.203 inches

**Width Between Flats:**

Between 0.554 inches and 0.564 inches

**Hole Diameter:**

Between 0.070 inches and 0.080 inches

**Grip Diameter:**

Between 0.3735 inches and 0.3745 inches

**End Application:**

Ng nav system

**Thread Diameter:**

0.3750 inches

**Grip Length:**

Between 1.178 inches and 1.198 inches

**Hole Quantity:**

3

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hole Configuration Style:**

Hexagon flats

**Surface Finish:**

32.0 microinches threads

**Product Name:**

Bolt, tension, hex head, close tolerance, a286 cres, short thread, reduced major diameter, self-locking and nonlocking, 160 ksi ftu

**Special Features:**

Finish is identified with green dye or paint on thread end; coverage may include the chamfer plus one incomplete thread

**Material:**

Iron alloy 660

**Material Specification:**

Ams5731, 5732, 5737 or ams5853 national std/spec single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type ii, class 2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas6303 through 6320 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0