

View Online at <https://aerobasegroup.com/nsn/5306-01-617-8366>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

1.938 inches

Fastener Length:

2.407 inches

Head Style:

Dished hexagon

Head Height:

Between 0.156 inches and 0.171 inches

Width Between Flats:

Between 0.492 inches and 0.502 inches

Hole Diameter:

0.070 inches

Grip Diameter:

Between 0.436 inches and 0.437 inches

Shank Unthreaded Hole Diameter:

0.076 inches all holes

Thread Diameter:

0.3125 inches

Grip Length:

1.000 inches

Hole Quantity:

3

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.226 inches all holes

Product Name:

Bolt, tension, hex head, close tolerance, alloy steel, long thread, reduced major dia., nonlocking, 160 ksi ftu; drilled shank

Material:

Steel comp 4140 or steel comp 4340 or steel comp 8740

Material Specification:

(4140) ams6349 or ams6382; (4340) 6415 or ams 6484; (8740) ams 6372 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Amsqq-p-416, tyii, cl ii, embrittlement req per nas4002 assn standard single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0