

View Online at <https://aerobasegroup.com/nsn/5306-01-619-7785>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.425 inches

**Fastener Length:**

0.925 inches

**Head Style:**

Double hexagon w/hole

**Head Height:**

Between 0.225 inches and 0.245 inches

**Width Between Flats:**

Between 0.347 inches and 0.361 inches

**Extended Washer Diameter:**

0.470 inches

**Extended Washer Thickness:**

Between 0.040 inches and 0.060 inches

**Hole Diameter:**

Between 0.038 inches and 0.042 inches

**Grip Diameter:**

Between 0.2481 inches and 0.2495 inches

**Single Shear Strength:**

95000 pounds per square inch

**Thread Diameter:**

0.250 inches

**Grip Length:**

0.500 inches

**Hole Quantity:**

2

**Hole Type:**

Drilled

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hole Configuration Style:**

Double hexagon longitudinal hole

**Material:**

Titanium alloy

**Material Specification:**

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

**Surface Treatment:**

Aluminum

**Surface Treatment Specification:**

Bms10-85, ty i, cl a mfr ref single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0