

View Online at <https://aerobasegroup.com/nsn/5306-01-619-7785>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.425 inches

Fastener Length:

0.925 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.225 inches and 0.245 inches

Width Between Flats:

Between 0.347 inches and 0.361 inches

Extended Washer Diameter:

0.470 inches

Extended Washer Thickness:

Between 0.040 inches and 0.060 inches

Hole Diameter:

Between 0.038 inches and 0.042 inches

Grip Diameter:

Between 0.2481 inches and 0.2495 inches

Single Shear Strength:

95000 pounds per square inch

Thread Diameter:

0.250 inches

Grip Length:

0.500 inches

Hole Quantity:

2

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

160000 pounds per square inch

Hole Configuration Style:

Double hexagon longitudinal hole

Material:

Titanium alloy

Material Specification:

Ams 4928 assn standard single material response or ams 4967 assn standard single material response

Surface Treatment:

Aluminum

Surface Treatment Specification:

Bms10-85, ty i, cl a mfr ref single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0